

FOR OFF ROAD/RACE USE ONLY!



Driven Rear Axle Block Sliders '15-'16 Ducati Scrambler ALL

Part#: DRAX-117

INSTALLATION INSTRUCTIONS

Removal:

1. Position bike in an upright position (preferably on a motorcycle work bench with a front wheel chock)
2. Loosen up the rear wheel axle nut.
3. Lift the rear of the bike off the ground.
4. Remove rear axle and rear wheel.
5. Remove OEM axle block.
6. Remove circle clip off OEM block and remove adjuster bolt (see FIG 1).

Brake Side

1. Reinstall adjuster bolt and circle clip into the driven blocks (set bolt at loose).
2. Position Driven Axle Blocks in bike and reinstall wheel and wheel axle.
3. Adjust chain tension following your owner's manual.
4. Torque axle to OEM specification.
5. Install slider pucks on axle blocks using blue Loctite.



FIG. 1

THIS PRODUCT IS INTENDED TO BE INSTALLED BY A CERTIFIED TECHNICIAN*

FOR OFF ROAD/RACE USE ONLY!



Driven Rear Axle Block Sliders '15-'16 Ducati Scrambler ALL

Part#: DRAX-117

INSTALLATION INSTRUCTIONS

Removal:

1. Position bike in an upright position (preferably on a motorcycle work bench with a front wheel chock)
2. Loosen up the rear wheel axle nut.
3. Lift the rear of the bike off the ground.
4. Remove rear axle and rear wheel.
5. Remove OEM axle block.
6. Remove circle clip off OEM block and remove adjuster bolt (see FIG 1).

Brake Side

1. Reinstall adjuster bolt and circle clip into the driven blocks (set bolt at loose).
2. Position Driven Axle Blocks in bike and reinstall wheel and wheel axle.
3. Adjust chain tension following your owner's manual.
4. Torque axle to OEM specification.
5. Install slider pucks on axle blocks using blue Loctite.



FIG. 1

THIS PRODUCT IS INTENDED TO BE INSTALLED BY A CERTIFIED TECHNICIAN*