

**FOR OFF ROAD/RACE USE ONLY!**



*Driven Rear Axle Block Sliders 2017 Yamaha R6*

*Part#: DRAX-118*

**INSTALLATION INSTRUCTIONS**

**Removal**

1. Position bike in an upright position (preferably on a motorcycle work bench with a front wheel chock and rear stand)
2. Loosen up the rear wheel axle nut.
3. Lift the rear of the bike off the ground.
4. Remove rear axle.
5. Remove OEM axle block.

**Installation**

**Sprocket Side:**

1. Locate part number 100512(engraved on the back of the part)
2. Install Driven Axle Block with the bolt hole facing down, install slider.

**Brake Side:**

1. Locate part number 100513(engraved on the back of the part)
2. Install Driven Axle Block with the bolt hole facing down, install slider.
3. Install axle nut washer.
4. Adjust chain tension following your owner's manual.
5. Torque slide to 45 ft/lbs using blue Loctite.

**THIS PRODUCT IS INTENDED TO BE INSTALLED BY A CERTIFIED TECHNICIAN\***

**FOR OFF ROAD/RACE USE ONLY!**



*Driven Rear Axle Block Sliders 2017 Yamaha R6*

*Part#: DRAX-118*

**INSTALLATION INSTRUCTIONS**

**Removal**

1. Position bike in an upright position (preferably on a motorcycle work bench with a front wheel chock and rear stand)
2. Loosen up the rear wheel axle nut.
3. Lift the rear of the bike off the ground.
4. Remove rear axle.
5. Remove OEM axle block.

**Installation**

**Sprocket Side:**

1. Locate part number 100512(engraved on the back of the part)
2. Install Driven Axle Block with the bolt hole facing down, install slider.

**Brake Side:**

1. Locate part number 100513(engraved on the back of the part)
2. Install Driven Axle Block with the bolt hole facing down, install slider.
3. Install axle nut washer.
4. Adjust chain tension following your owner's manual.
5. Torque slide to 45 ft/lbs using blue Loctite.

**THIS PRODUCT IS INTENDED TO BE INSTALLED BY A CERTIFIED TECHNICIAN\***