FOR OFF ROAD/RACE USE ONLY!



Part#:DTI-XX INSTALLATION INSTRUCTIONS

Tools needed:

- 1. Wire stripper
- 2. Crimp tool



What comes in a kit: 1. Turn Signal kit



THIS PRODUCT IS INTENDED TO BE INSTALLED BY A CERTIFIED TECHNICIAN*


FOR OFF ROAD/RACE USE ONLY!



Part#:DTI-XX INSTALLATION INSTRUCTIONS

Tools needed:

- 1. Wire stripper
- 2. Crimp tool



What comes in a kit: 1. Turn Signal kit



THIS PRODUCT IS INTENDED TO BE INSTALLED BY A CERTIFIED TECHNICIAN*

FOR OFF ROAD/RACE USE ONLY!



Turn Signal Installation:

- Remove stock turn signals
- Locate power and common wire on o.e. harness
- Cut stock leads
- Slide shrink tube (supplied) onto wires
- Strip ends
- Crimp female leads on wires. Put shrink tube on fig.1
- Connect wires and test for proper operation

NOTE: If blink rate is too fast, a resistor will be required






Resistor Installation:

- Connect resistor female leads to turn signal male connectors parallel fig.2
- Connect resistor male connectors to bike wire harness

NOTE: If you don't wish to use resistors, we offer an LED flasher. This flasher will only work on bikes with a 2 lead flasher.



THIS PRODUCT IS INTENDED TO BE INSTALLED BY A CERTIFIED TECHNICIAN*

FOR OFF ROAD/RACE USE ONLY!

Turn Signal Installation:

- Remove stock turn signals
- Locate power and common wire on o.e. harness
- Cut stock leads
- Slide shrink tube (supplied) onto wires
- Strip ends
- Crimp female leads on wires. Put shrink tube on fig.1
- Connect wires and test for proper operation

NOTE: If blink rate is too fast, a resistor will be required

Resistor Installation:


- Connect resistor female leads to turn signal male connectors parallel fig.2
- Connect resistor male connectors to bike wire harness

NOTE: If you don't wish to use resistors, we offer an LED flasher. This flasher will only work on bikes with a 2 lead flasher.





(fig. 1)



THIS PRODUCT IS INTENDED TO BE INSTALLED BY A CERTIFIED TECHNICIAN*