

PART#: DSBLOCK 14

(Installation Instructions)

- 1. Make sure ignition key is turned to the off position and engine is cool.
- 2. Place motorcycle on lift, rear stand, or side stand.
- 3. Locate the final destination of the new block off plates. (right hand side in the front of cylinder), (left hand side in the rear of cylinder)
- Carefully remove any fairings/parts obstructing the OEM plates and then remove them.
- Using blue Loctite, install the new block off plates using the OEM hardware, and the OEM sealing "O rings" if present.
- Disconnect the two hoses from the solenoid.
- Disconnect the hose going from the solenoid to the airbox and use the cap provided to plug the airbox.
- 8. Carefully replace any pieces removed during installation.

Do not unplug the solenoid. If it is unplugged it will trigger the "FI" warning light.



PART#: DSBLOCK 14

(Installation Instructions)

- 1. Make sure ignition key is turned to the off position and engine is cool.
- 2. Place motorcycle on lift, rear stand, or side stand.
- Locate the final destination of the new block off plates. (right hand side in the front of cylinder), (left hand side in the rear of cylinder)
- Carefully remove any fairings/parts obstructing the OEM plates and then remove them.
- Using blue Loctite, install the new block off plates using the OEM hardware, and the OEM sealing "O rings" if present.
- 6. Disconnect the two hoses from the solenoid.
- Disconnect the hose going from the solenoid to the airbox and use the cap provided to plug the airbox.
- 8. Carefully replace any pieces removed during installation.

Do not unplug the solenoid. If it is unplugged it will trigger the "FI" warning light.

DRIVEN REQUIRES THIS PRODUCT TO BE INSTALLED BY A CERTIFIED TECHNICIAN

NOT INTENDED FOR STREET/HIGHWAY USE! FOR OFF ROAD/RACE USE ONLY!

DRIVEN PERFORMANCE PRODUCTS WWW.DRIVENRACING.COM 866-5-DRIVEN DRIVEN REQUIRES THIS PRODUCT TO BE INSTALLED BY A CERTIFIED TECHNICIAN

NOT INTENDED FOR STREET/HIGHWAY USE! FOR OFF ROAD/RACE USE ONLY!

DRIVEN PERFORMANCE PRODUCTS WWW.DRIVENRACING.COM 866-5-DRIVEN



PART#: DSBLOCK 14

(Installation Instructions)

- 1. Make sure ignition key is turned to the off position and engine is cool.
- 2. Place motorcycle on lift, rear stand, or side stand.
- 3. Locate the final destination of the new block off plates. (right hand side in the front of cylinder), (left hand side in the rear of cylinder)
- Carefully remove any fairings/parts obstructing the OEM plates and then remove them.
- Using blue Loctite, install the new block off plates using the OEM hardware, and the OEM sealing "O rings" if present.
- 6. Disconnect the two hoses from the solenoid.
- Disconnect the hose going from the solenoid to the airbox and use the cap provided to plug the airbox.
- 8. Carefully replace any pieces removed during installation.

Do not unplug the solenoid. If it is unplugged it will trigger the "FI" warning light.



PART#: DSBLOCK 14

(Installation Instructions)

- 1. Make sure ignition key is turned to the off position and engine is cool.
- 2. Place motorcycle on lift, rear stand, or side stand.
- 3. Locate the final destination of the new block off plates. (right hand side in the front of cylinder), (left hand side in the rear of cylinder)
- Carefully remove any fairings/parts obstructing the OEM plates and then remove them.
- Using blue Loctite, install the new block off plates using the OEM hardware, and the OEM sealing "O rings" if present.
- 6. Disconnect the two hoses from the solenoid.
- Disconnect the hose going from the solenoid to the airbox and use the cap provided to plug the airbox.
- 8. Carefully replace any pieces removed during installation.

Do not unplug the solenoid. If it is unplugged it will trigger the "FI" warning light.

DRIVEN REQUIRES THIS PRODUCT TO BE INSTALLED BY A CERTIFIED TECHNICIAN

NOT INTENDED FOR STREET/HIGHWAY USE! FOR OFF ROAD/RACE USE ONLY!

NOT INTENDED FOR STREET/HIGHWAY USE! FOR OFF ROAD/RACE USE ONLY!

DRIVEN REQUIRES THIS PRODUCT TO BE INSTALLED BY A CERTIFIED TECHNICIAN



